

# SIG-CLI DeepDive - Kubectl Plugins

Maciej Szulik, Juan Vallejo – Red Hat

@soltysh

@juanvallejo



kubernetes




# What are plugins?

@soltys @juanvallejo



# "Old" plugins?



# Plugins - take two



UX

Discoverability

“Extending” built-ins (?)

<https://unsplash.com>

@soltys @juanvallejo



# Plugins are now beta!

Find out more

# How to write your own?

Any binary




**PATH + kubectl-\***

@soltys @juanvallejo



# Any language



[k8s.io/cli-runtime](https://k8s.io/cli-runtime)

@soltys @juanvallejo



# CLI Runtime - features



Same core utils that **kubectl** commands use

Reading configuration

Clients to talk to API server

[k8s.io/cli-runtime](https://k8s.io/cli-runtime)



@soltys @juanvallejo



# CLI Runtime - features



Bind flags (printing, config, etc.)

Printing utilities (json, yaml, etc.)

Set of polymorphic helpers



[k8s.io/cli-runtime](https://k8s.io/cli-runtime)

@soltys @juanvallejo



# Naming structure



[kubernetes/enhancements/keps/sig-cli/](#)  
[0024-kubectl-plugins.md](#)

@soltys @juanvallejo



# Naming structure



**kubectl-foo-bar**

**kubectl-login**

**kubectl-my\_plugin**



**kubectl foo bar**

**kubectl login**

**kubectl my-plugin**





# Name conflicts & path order

PATH=/usr/bin/plugins:/usr/bin/moreplugins

1. /bin/plugins/kubectl-foo ➡️
2. ~~/bin/moreplugins/kubectl-foo~~





# Name conflicts & greedy matching

PATH=/usr/bin/plugins:/usr/bin/moreplugins

```
$ kubectl foo bar baz
```

1. "*baz*" becomes arg
2. /bin/moreplugins/kubectl-foo-bar
3. ~~/bin/plugins/kubectl-foo~~





# Sample plugin

```
func main() {
    flags := pflag.NewFlagSet("kubectl-ns", pflag.ExitOnError)
    pflag.CommandLine = flags

    root := cmd.NewCmdNamespace(genericclioptions.IOStreams{In: os.Stdin, Out: os.Stdout, ErrOut: os.Stderr})
    if err := root.Execute(); err != nil {
        os.Exit(1)
    }
}
```

[k8s.io/sample-cli-plugin](https://k8s.io/sample-cli-plugin)

@soltys @juanvallejo





# Sample plugin - anatomy

## Key Imports

```
"k8s.io/client-go/tools/clientcmd"
```



KUBECONFIG manipulation

```
"k8s.io/client-go/tools/clientcmd/api"
```



KUBECONFIG types

```
"k8s.io/cli-runtime/pkg/genericclioptions"
```



Generic helpers

```
)
```





# Sample plugin - anatomy

## Bind Config Flags

```
&NamespaceOptions{  
    configFlags: genericclioptions.NewConfigFlags(),  
  
    o.configFlags.AddFlags(cmd.Flags())  
  
    return cmd
```

@soltys @juanvallejo





# Sample plugin - anatomy

## Obtain KUBECONFIG data

```
var err error
o.rawConfig, err = o.configFlags.ToRawKubeConfigLoader().RawConfig()
if err != nil {
    return err
}
```

@soltys @juanvallejo



A photograph of a person standing in a field of tall grass, looking up at a dramatic sunset sky. The sky is filled with wispy clouds colored in shades of orange, pink, and blue. The person is wearing a dark hoodie and pants, standing with their hands behind their back. The horizon shows a line of trees.

# Future?



**Regular SIG Meeting: Wednesdays at 09:00 PT  
(Pacific Time) (biweekly).**

**Reach out on the SIG CLI Slack Channel (#sig-cli)**

**Contact us through our email group:  
[kubernetes-sig-cli@googlegroups.com](mailto:kubernetes-sig-cli@googlegroups.com)**

@soltys @juanvallejo

