



KubeCon



CloudNativeCon


Europe 2018

 HYPER.SH

CRI: The Second Boom of Container Runtimes

Xu Wang (@gnawux)

Lei Zhang (@resouer)



Agenda



KubeCon



CloudNativeCon

Europe 2018

- CRI Deep Dive
- The Current CRI Implementations
- CRI and Kata Containers




A Brief History of CRI



Europe 2018

- Once upon a time...
 - rkt was added into kubelet as the 2nd runtime.
 - Increased the complexity on maintenance
 - Docker (the 1st runtime) introduced more and more feature.
 - Don't like a simple runtime any more
 - Hyper.sh joined the community and tried to become a third runtime.



Closed [Jump to bottom](#)

Add a client/server implementation of the container runtime #13768

 **brendanburns** opened this issue over 2 years ago

[area/extensibility](#) [priority/awaiting-more-evidence](#) [sig/node](#)

Currently, any container runtime has to be linked into the kubelet. This makes experimentation difficult, and prevents users from landing an alternate container runtime without landing code in core kubernetes.

To facilitate experimentation and to enable user choice, we should add a client/server implementation of the container runtime interface.

This implementation will simply encode the requests, send them to a server where they will be decoded and sent into an instance of the container runtime interface.

However, this enables container runtime implementations to be built and maintained outside of the core kubernetes tree.

[@dchen1107](#) [@smarterclayton](#)
[@kubernetes/goog-node](#)



The Birth of CRI



KubeCon



CloudNativeCon

Europe 2018



The Kubelet should not vendor a runtime implementation.

(Unfortunately, this is not the original words literally)


- Developers from Google, CoreOS, and Hyper.sh drafted a kubelet-runtime interface together.
- The interface, CRI, was written with gRPC
 - gRPC had already been open sourced at that time.
 - The performance difference between gRPC and HTTP/REST was tested
- First CRI implementation: dockershim
- First Non-Docker CRI implementation: Frakti



The CRI Interface



Europe 2018



- Describe what kubelet expects from container runtimes
- Imperative container-centric interface
- Extensibility





KubeCon




CloudNativeCon

Europe 2018



Implement a CRI Runtime (1)

Lifecycle

```
$ kubectl run foo ..
```



1. RunPodSandbox(foo)
2. CreatContainer(A)
3. StartContainert(A)
4. CreatContainer(B)
5. StartContainer(B)



Implement a CRI Runtime (2)




KubeCon



CloudNativeCon

Europe 2018

Streaming





KubeCon



CloudNativeCon

Europe 2018



The Existing CRI Runtimes

CRI-O, cri-containerd, frakti, and how they work



The Existing CRI Runtimes



KubeCon



CloudNativeCon

Europe 2018

- containerd/cri (cri-containerd)
 - containerd and k8s node team
- CRI-O
 - Red Hat etc.
- frakti
 - Hyper.sh etc.



Containerd (w/ cri plugin) in brief




KubeCon



CloudNativeCon

Europe 2018



CRI-O in brief




KubeCon



CloudNativeCon

Europe 2018



Similar to Containerd, right?



Frakti 1.0 in brief




KubeCon



CloudNativeCon

Europe 2018



- Frakti is a CRI shim
- Hyperd implements the CRI semantics for runV





KubeCon



CloudNativeCon

Europe 2018

 HYPER.SH

CRI and Kata Containers



History of Kata




KubeCon



CloudNativeCon

Europe 2018



*Other names and brands may be claimed as the property of others.



Technical Vision of Kata



KubeCon



CloudNativeCon

Europe 2018

- Light and fast VM-based containers
- Merge Intel® Clear Containers and Hyper runV technologies
- Seamless integration with Kubernetes (CRI), Docker and Openstack
- Support multiple architectures
- Support multiple hypervisors



How Kata Works




KubeCon



CloudNativeCon

Europe 2018

- Each container/pod is hypervisor isolated
- As secure as a VM
- As fast as a container
- Seamless integration with the container ecosystem and management layers



*Other names and brands may be claimed as the property of others.



CRI for Kata Containers



KubeCon



CloudNativeCon

Europe 2018

- Kata Containers is designed to be compatible with Kubernetes
- Integration Methods
 - Kata Containers as a standalone tool
 - runC compatible command line
 - OCI specs
 - Work with containerd and CRI-O
 - Kata Containers as a runtime lib
 - runV compatible APIs
 - Work with frakti
 - (containerd plugin?)



containerd/CRI-O + Kata




KubeCon



CloudNativeCon

Europe 2018



Frakti + Kata




KubeCon



CloudNativeCon

Europe 2018



Comparison



KubeCon



CloudNativeCon

Europe 2018

- Share more code parts
- Shims and Proxy Process
 - Process
 - Memory
- And more resources
 - Rootfs and Volumes
 - Networking plug-ins





KubeCon



CloudNativeCon

Europe 2018

h_ HYPER.SH

Thank You

