

Session 6 - Spatial Data

R for Data Analysis

DIME Analytics

The World Bank – DIME | [WB Github](#)

April 2025



Table of contents


1. Overview of GIS concepts
2. Load and explore polygons, polylines, and points
3. Static maps
4. Interactive maps
5. Spatial operations applied on one dataset
6. Spatial operations applied on multiple datasets

Overview of GIS concepts

Spatial data: The two main types of spatial data are **vector data** and **raster data**


Vector data

- Points, lines, or polygons
- Common file formats include shapefiles (.shp) and geojsons (.geojson)
- Examples: polygons on countries, polylines of roads, points of schools




Raster data

- Spatially referenced grid
- Common file format is a geotif (.tif)
- Example: Satellite imagery of nighttime lights



Coordinate Reference Systems (CRS)

- Coordinate reference systems use pairs of numbers to define a location on the earth
- For example, the World Bank is at a latitude of 38.89 and a longitude of -77.04



Coordinate Reference Systems (CRS)

There are many different coordinate reference systems, which can be grouped into **geographic** and **projected** coordinate reference systems. Geographic systems live on a sphere, while projected systems are “projected” onto a flat surface.

Geographic (Sphere)



40°W, 40°N

Projected (Flat)




Geographic Coordinate Systems

Units: Defined by latitude and longitude, which measure angles and units are typically in decimal degrees. (Eg, angle is latitude from the equator).

Latitude & Longitude:


- On a grid X = longitude, Y = latitude; sometimes represented as (longitude, latitude).
- Also has become convention to report them in alphabetical order: (latitude, longitude) — such as in Google Maps.
- Valid range of latitude: -90 to 90
- Valid range of longitude: -180 to 180
- **{Tip}** Latitude sounds (and looks!) like latter.



Geographic Coordinate Systems

Distance on a sphere

- At the equator (latitude = 0), a 1 decimal degree longitude distance is about 111km; towards the poles (latitude = -90 or 90), a 1 decimal degree longitude distance converges to 0 km.
- We must be careful (ie, use algorithms that account for a spherical earth) to calculate distances! The distance along a sphere is referred to as a **great circle distance**.
- Multiple options for spherical distance calculations, with trade-off between accuracy & complexity. (See distance section for details).





Geographic Coordinate Systems

Datums

- **Is the earth flat?** No!
- **Is the earth a sphere?** No!
- **Is the earth a lumpy ellipsoid?** Yes!

The earth is a lumpy ellipsoid, a bit flattened at the poles.

- A **datum** is a model of the earth that is used in mapping. One of the most common datums is **WGS 84**, which is used by the Global Positional System (GPS).
- A datum is a reference ellipsoid that approximates the shape of the earth.
- Other datums exist, and the latitude and longitude values for a specific location will be different depending on the datum.



Projected Coordinate Systems

Projected coordinate systems project spatial data from a 3D to 2D surface.

Distortions: Projections will distort some combination of distance, area, shape or direction. Different projections can minimize distorting some aspect at the expense of others.



Units: When projected, points are represented as “northings” and “eastings.” Values are often represented in meters, where northings/eastings are the meter distance from some reference point. Consequently, values can be very large!

Datums still relevant: Projections start from some representation of the earth. Many projections (eg, [UTM](#)) use the WGS84 datum as a starting point (ie, reference datum), then project it onto a flat surface.

Click [here](#) to see why Toby & CJ are confused (hint: projections!)



Projected Coordinate Systems



Referencing coordinate reference systems

- There are many ways to reference coordinate systems, some of which are verbose.
- **PROJ** (Library for projections) way of referencing WGS84 `+proj=longlat`
`+datum=WGS84 +no_defs +type=crs`
- **EPSG** Assigns numeric code to CRSs to make it easier to reference. Here, WGS84 is `4326`.

Coordinate Reference Systems

Whenever have spatial data, need to know which coordinate reference system (CRS) the data is in.

- You wouldn't say **"I am 5 away"**
- You would say **"I am 5 [miles / kilometers / minutes / hours] away"** (units!)
- Similarly, a "complete" way to describe location would be: I am at **6.51 latitude, 3.52 longitude using the WGS 84 CRS**

Introduction

- This session could be a whole course on its own, but we only have an hour and half.
- To narrow our subject, we will focus on only one type of spatial data, vector data.
- This is the most common type of spatial data that non-GIS experts will encounter in their work.
- We will use the `sf` package, which is the tidyverse-compatible package for geospatial data in R.
- For visualizing, we'll rely on `ggplot2` for static maps and `leaflet` for interactive maps

Setup

If You Attended Session 2

If You Did Not Attend Session 2

1. Copy/paste the following code into a new RStudio script:

```
install.packages("usethis")  
library(usethis)  
usethis::use_zip(  
  "https://github.com/worldbank/dime-r-training/archive/main.zip",  
  cleanup = TRUE  
)
```

Copy Code

2. A new RStudio environment will open. Use this for the session today.

Setup

Install new packages


```
install.packages(c("sf",  
                  "leaflet",  
                  "geosphere"),  
                dependencies = TRUE)
```

And load them

```
library(here)  
library(tidyverse)  
library(sf)      # Simple features  
library(leaflet) # Interactive map  
library(geosphere) # Great circle distances
```

Load and explore polylines, polygons, and points

The main package we'll rely on is the `sf` (simple features) package. With `sf`, spatial data is structured similarly to a **dataframe**; however, each row is associated with a **geometry**. Geometries can be one of the below types.



Load and explore polygon

The first thing we will do in this session is to recreate this data set:

```
country_sf <-  
  st_read(here("DataWork",  
              "DataSets",  
              "Final",  
              "country.geojson"))
```

```
## Reading layer `country' from data source `C:\WBG\repos\dime-r-training\DataWork\DataSets\Final\country.geojson' using  
## Simple feature collection with 300 features and 13 fields  
## Geometry type: MULTIPOLYGON  
## Dimension:      XY  
## Bounding box:   xmin: 33.90959 ymin: -4.720417 xmax: 41.92622 ymax: 5.061166  
## Geodetic CRS:   WGS 84
```

Exploring the data

Look at first few observations

```
head(country_sf)
```

```
## Simple feature collection with 6 features and 13 fields
```

```
## Geometry type: MULTIPOLYGON
```

```
## Dimension:      XY
```

```
## Bounding box:   xmin: 35.52292 ymin: -0.198901 xmax: 36.29659 ymax: 0.990413
```

```
## Geodetic CRS:   WGS 84
```

```
##      GID_2 GID_0 COUNTRY  GID_1  NAME_1 NL_NAME_1      NAME_2 VARNAME_2 NL_NAME_2      TYPE_2  ENGTYPE_2
## 1 KEN.1.1_1  KEN   Kenya KEN.1_1 Baringo      <NA>      805      <NA>      <NA> Constituency Constituency
## 2 KEN.1.2_1  KEN   Kenya KEN.1_1 Baringo      <NA> Baringo Central <NA>      <NA> Constituency Constituency
## 3 KEN.1.3_1  KEN   Kenya KEN.1_1 Baringo      <NA> Baringo North  <NA>      <NA> Constituency Constituency
## 4 KEN.1.4_1  KEN   Kenya KEN.1_1 Baringo      <NA> Baringo South  <NA>      <NA> Constituency Constituency
## 5 KEN.1.5_1  KEN   Kenya KEN.1_1 Baringo      <NA> Eldama Ravine <NA>      <NA> Constituency Constituency
## 6 KEN.1.6_1  KEN   Kenya KEN.1_1 Baringo      <NA> Mogotio      <NA>      <NA> Constituency Constituency
##   CC_2 HAS_2      geometry
## 1  162  <NA> MULTIPOLYGON (((35.87727 -0...
## 2  159  <NA> MULTIPOLYGON (((35.7977 0.3...
## 3  158  <NA> MULTIPOLYGON (((35.81346 0....
## 4  160  <NA> MULTIPOLYGON (((36.22934 0....
```

Exploring the data

Number of rows

```
nrow(country_sf)
```

```
## [1] 300
```

Exploring the data

Check coordinate reference system


```
st_crs(country_sf)
```

```
## Coordinate Reference System:
##   User input: WGS 84
##   wkt:
##   GEOGCRS["WGS 84",
##     DATUM["World Geodetic System 1984",
##       ELLIPSOID["WGS 84",6378137,298.257223563,
##         LENGTHUNIT["metre",1]]],
##     PRIMEM["Greenwich",0,
##       ANGLEUNIT["degree",0.0174532925199433]],
##     CS[ellipsoidal,2],
##       AXIS["geodetic latitude (Lat)",north,
##         ORDER[1],
##         ANGLEUNIT["degree",0.0174532925199433]],
##       AXIS["geodetic longitude (Lon)",east,
##         ORDER[2],
##         ANGLEUNIT["degree",0.0174532925199433]],
##     ID["EPSG",4326]]
```

Exploring the data

Plot the data. To plot using `ggplot2`, we use the `geom_sf` geometry.

```
ggplot() +  
  geom_sf(data = country_sf)
```



Attributes of data

We want the area of each location, but we don't have a variable for area

```
names(country_sf)
```

```
## [1] "GID_2"      "GID_0"      "COUNTRY"    "GID_1"      "NAME_1"     "NL_NAME_1"  "NAME_2"     "VARNAME_2"  "NL_NAME_2"
## [10] "TYPE_2"     "ENGTYPE_2"  "CC_2"       "HASC_2"     "geometry"
```

Attributes of data

Determine area. Note the CRS is spherical (WGS84), but `st_area` gives area in meters squared. R uses s2 geometry for this.

```
st_area(country_sf)
```

```
## Units: [m^2]
```

```
## [1] 174612548 664171032 1640235288 1893541200 909726196 1162391322 4446442673 244343146 319588761
## [10] 546475821 791703635 487034695 347077424 234870080 320531683 178295354 302805234 267396640
## [19] 950722974 208724111 377069605 235040170 166654802 311166355 244842707 270856300 195816268
## [28] 234613620 250070745 300226047 544675636 890441628 819095221 562423505 473818437 774008353
## [37] 1329273270 340468166 4248579388 7557295525 16712310204 603028994 8442761951 6483073596 270237144
## [46] 247974418 626536513 259329880 1032562720 699140857 292011673 1147576864 124531035 15430646699
## [55] 10122778443 4333824029 3283326674 112849413 6385975697 7975956018 210204075 144513355 145118575
## [64] 102257259 162397218 424754069 278291541 175812288 138974871 258559234 412385494 246642948
## [73] 447240937 317315791 755656427 354432319 466560197 244100323 214221442 184422278 336670907
## [82] 59209638 79588059 106276706 172477093 468135485 283853034 204126728 232219564 2950195157
## [91] 703903982 832269572 436237078 6970056180 614090663 201415848 544469250 238375984 550503547
## [100] 230810950 241653749 114996036 102453209 127269592 131050389 98022999 136597611 160116397
## [109] 208693101 72147288 162435042 313730881 667098008 404328975 605968535 451077270 524062466
## [118] 4747798919 1728598186 12776321776 648117269 4706652226 4718665995 743726578 4967043891 2033955496
## [127] 953096770 462893878 1403369302 5320660807 2842965457 2531222550 4218803604 171732132 206956593
## [136] 521665804 1403310114 583520262 846378092 1023316734 238773253 1065648936 406103613 2322255189
```

Operations similar to dataframes


Create new dataset that captures locations for one administrative region

```
city_sf <- country_sf %>%  
  filter(NAME_1 == "Nairobi")
```

Operations similar to dataframes

Plot the dataframe

```
ggplot() +  
  geom_sf(data = city_sf)
```



Load and explore polyline

Exercise:

- Load the roads data `roads.geojson` and name the object `roads_sf`
- Look at the first few observations
- Check the coordinate reference system
- Map the polyline

Solution:

```
roads_sf <- st_read(here("DataWork", "DataSets", "Final", "roads.geojson"))  
  
head(roads_sf)  
  
st_crs(roads_sf)  
  
ggplot() +  
  geom_sf(data = roads_sf)
```

Load and explore polyline

```
roads_sf <-  
  st_read(here("DataWork",  
              "DataSets",  
              "Final",  
              "roads.geojson"))
```

```
## Reading layer `roads' from data source `C:\WBG\repos\dime-r-training\DataWork\DataSets\Final\roads.geojson' using driver 'GeoJSON'  
## Simple feature collection with 3326 features and 3 fields  
## Geometry type: MULTILINESTRING  
## Dimension:      XY  
## Bounding box:   xmin: 36.68034 ymin: -1.430759 xmax: 37.07664 ymax: -1.162558  
## Geodetic CRS:   WGS 84
```

```
ggplot() +  
  geom_sf(data = roads_sf)
```



Load and explore polyline

Exercise: Determine length of each line (hint: use `st_length`)

Solution:

```
st_length(roads_sf)
```

```
## Units: [m]
```

```
##      [1]  901.575669  137.859146  166.089698   24.263358  174.355741  482.550326  486.250661   64.104259  615.457423
##     [10]   16.713533   19.698716    3.848732    4.123779  555.445488  551.580925    7.064828  229.565489  588.930451
##     [19]  136.944584  579.132204   58.331756   21.793644   90.157091   41.250716   81.708553   68.324169  496.357721
##     [28]   14.151642   44.035735   45.810017   41.676861   35.126049   40.577592   43.183338 1068.724720  254.986241
##     [37]  554.188242  280.010314  573.652511  632.206308  903.432072   15.215667   84.991640   89.585364   39.362830
##     [46]  656.439901  562.994183   53.046523   55.049084   22.151381  157.276691  742.136179  255.684125  188.665891
##     [55]  196.867732  322.574154  136.879449  145.136229 1123.879549  449.762113   76.812840  425.625306   83.281411
##     [64]   67.480452   68.962106  537.993328   19.378576  103.228193   59.214009   26.159881  384.184839  349.081270
##     [73]   23.398508   34.330123   28.640061   22.090503  126.496308  638.049903 1026.044009   19.196929  259.895071
##     [82]  372.237351   42.319444  456.900234   87.612555 1531.397856  271.171558  325.272260  236.299712  10.440361
##     [91]   92.495221  379.530644    7.949999  622.409572   15.109525  142.737712  107.081783   33.467081  62.377601
##    [100]  724.000829  695.581295   65.014153  179.260849  195.899725  100.995000  316.149423   86.934045  70.416399
```

01:00

Load and explore point data

We'll load a dataset of the location of schools

```
schools_df <-  
  read_csv(here("DataWork",  
               "DataSets",  
               "Final",  
               "schools.csv"))
```

```
## Rows: 3546 Columns: 5
```

```
## — Column specification
```

```
## Delimiter: ","
```

```
## chr (2): name, amenity
```

```
## dbl (3): osm_id, longitude, latitude
```

```
##
```

```
## i Use `spec()` to retrieve the full column specification for this data.
```

```
## i Specify the column types or set `show_col_types = FALSE` to quiet this message.
```

Explore data

```
head(schools_df)
```

```
## # A tibble: 6 × 5
##       osm_id name          amenity longitude latitude
##       <dbl> <chr>          <chr>      <dbl>    <dbl>
## 1  30312225 Consolata School school      36.8    -1.27
## 2  674552830 <NA>            <NA>      36.8    -1.26
## 3 1399125354 Galitos restaurant school      36.8    -1.29
## 4 1764153756 Makini Schools school      36.8    -1.30
## 5 1867185524 Bohra Primary School school      36.8    -1.26
## 6 2061462027 <NA>            <NA>      36.8    -1.26
```

Explore data

```
names(schools_df)
```

```
## [1] "osm_id"      "name"        "amenity"     "longitude"  "latitude"
```

Convert to spatial object

We define the (1) coordinates (longitude and latitude) and (2) CRS. **Note:** We must determine the CRS from the data metadata. This dataset comes from OpenStreetMaps, which uses EPSG:4326.

Assigning the incorrect CRS is one of the most common sources of issues I see with geospatial work. If something looks weird, check the CRS!

```
schools_sf <- st_as_sf(schools_df,  
                      coords = c("longitude", "latitude"),  
                      crs = 4326)
```

Convert to spatial object

```
head(schools_sf$geometry)
```

```
## Geometry set for 6 features
```

```
## Geometry type: POINT
```

```
## Dimension:      XY
```

```
## Bounding box:   xmin: 36.76877 ymin: -1.296051 xmax: 36.80406 ymax: -1.258515
```

```
## Geodetic CRS:   WGS 84
```

```
## First 5 geometries:
```

```
## POINT (36.80406 -1.267486)
```

```
## POINT (36.79734 -1.25969)
```


```
## POINT (36.77077 -1.290325)
```

```
## POINT (36.76877 -1.296051)
```

```
## POINT (36.79066 -1.258515)
```


Map points object: Using sf

```
ggplot() +  
  geom_sf(data = schools_sf)
```



Map points object: Using dataframe

```
ggplot() +  
  geom_point(data = schools_df,  
            aes(x = longitude,  
                y = latitude))
```




Make better static map

Lets make a better static map.

```
# Adding a variable with squared km
city_sf <- city_sf %>%
  mutate(area_m = city_sf %>% st_area() %>% as.numeric(),
         area_km = area_m / 1000^2)


# Plotting
ggplot() +
  geom_sf(data = city_sf,
         aes(fill = area_km)) +
  labs(fill = "Area") +
  scale_fill_distiller(palette = "Blues") +
  theme_void()
```



Make better static map

Lets add another spatial layer

```
ggplot() +  
  geom_sf(data = city_sf,  
          aes(fill = area_km)) +  
  geom_sf(data = schools_sf,  
          aes(color = "Schools")) +  
  labs(fill = "Area",  
        color = NULL) +  
  scale_fill_distiller(palette = "Blues") +  
  scale_color_manual(values = "black") +  
  theme_void()
```



Another static map

Exercise: Make a static map of roads, coloring each road by its type. (**Hint:** The `highway` variable indicates the type).

Solution:

```
ggplot() +  
  geom_sf(data = roads_sf,  
          aes(color = highway)) +  
  theme_void() +  
  labs(color = "Road Type")
```



Road Type

— motorway

— motorway_link

01:00

Another static map

```
ggplot() +  
  geom_sf(data = roads_sf,  
          aes(color = highway)) +  
  theme_void() +  
  labs(color = "Road Type")
```



Road Type


- motorway
- motorway_link
- primary
- secondary
- secondary_link
- tertiary

Interactive map

We use the `leaflet` package to make interactive maps. Leaflet is a JavaScript library, but the `leaflet` R package allows making interactive maps using R. Use of leaflet somewhat mimics how we use ggplot.

- Start with `leaflet()` (instead of `ggplot()`)
- Add spatial layers, defining type of layer (similar to geometries)

```
leaflet() %>%  
  addTiles() # Basemap
```



Interactive map

We use the `leaflet` package to make interactive maps. Leaflet is a JavaScript library, but the `leaflet` R package allows making interactive maps using R. Use of leaflet somewhat mimics how we use ggplot.

- Start with `leaflet()` (instead of `ggplot()`)
- Add spatial layers, defining type of layer (similar to geometries)

```
leaflet() %>%  
  addTiles() %>%  
  addPolygons(data = city_sf)
```



Interactive map

Add a pop-up

```
leaflet() %>%  
  addTiles() %>%  
  addPolygons(data = city_sf,  
              popup = ~NAME_2)
```



Interactive map

Add more than one layer

```
leaflet() %>%  
  addTiles() %>%  
  addPolygons(data = city_sf,  
              popup = ~NAME_2) %>%  
  addCircles(data = schools_sf,  
             popup = ~name,  
             color = "black")
```



Interactive map of roads

Exercise: Create a leaflet map with roads, using the `roads_sf` dataset. (**Hint:** Use `addPolylines()`)

Solution:

```
leaflet() %>%  
  addTiles() %>%  
  addPolylines(data = roads_sf)
```

02:00

Interactive map of roads

```
leaflet() %>%  
  addTiles() %>%  
  addPolylines(data = roads_sf)
```



Interactive maps

We can spend lots of time going over what we can do with leaflet - but that would take up too much time. [This resource](#) provides helpful tutorials for things like:

- Changing the basemap
- Adding colors
- Adding a legend
- And much more!

Spatial operations applied on single dataset

- `st_transform`: Transform CRS
- `st_buffer`: Buffer point/line/polygon
- `st_combine`: Dissolve by attribute
- `st_convex_hull`: Create convex hull
- `st_centroid`: Create new sf object that uses the centroid
- `st_drop_geometry`: Drop geometry; convert from sf to dataframe
- `st_coordinates`: Get matrix of coordinates
- `st_bbox`: Get bounding box

Transform CRS

The schools dataset is currently in a geographic CRS (WGS84), where the units are in decimal degrees. We'll transform the CRS to a projected CRS ([EPSG:32632](#)), and where the units will be in meters.

Note that coordinate values are large! Values are large because units are in meters. Large coordinate values suggest projected CRS; latitude is between -90 and 90 and longitude is between -180 and 180.

```
schools_utm_sf <- st_transform(schools_sf, 32632)

schools_utm_sf$geometry %>% head(2) %>% print()

## Geometry set for 2 features
## Geometry type: POINT
## Dimension:      XY
## Bounding box:   xmin: 3722217 ymin: -158522.3 xmax: 3723051 ymax: -157537.6
## Projected CRS: WGS 84 / UTM zone 32N


## POINT (3723051 -158522.3)

## POINT (3722217 -157537.6)
```

Buffer

We have the points of schools. Now we create a 1km buffer around schools.


```
schools_1km_sf <- schools_sf %>%  
  st_buffer(dist = 1000) # Units are in meters. Thanks s2!  
  
ggplot() +  
  geom_sf(data = schools_1km_sf)
```



Dissolve by an attribute

Below we have the second administrative regions. Using this dataset, let's create a new object at the first administrative region level.

```
country_1_sf <- country_sf %>%  
  group_by(NAME_1) %>%  
  summarise(geometry = st_combine(geometry)) %>%  
  ungroup()  
  
ggplot() +  
  geom_sf(data = country_1_sf)
```



Exercise

Exercise: Create a polyline of all trunk roads (dissolve it using `st_combine`), and buffer the polyline by 10 meters. In `roads_sf`, the `highway` variable notes road types.

Solution:

```
roads_sf %>%  
  filter(highway == "trunk") %>%  
  summarise(geometry = st_combine(geometry)) %>%  
  st_buffer(dist = 10)
```

```
## Simple feature collection with 1 feature and 0 fields  
## Geometry type: MULTIPOLYGON  
## Dimension: XY  
## Bounding box: xmin: 36.68359 ymin: -1.430867 xmax: 37.07692 ymax: -1.204784  
## Geodetic CRS: WGS 84  
##  
## geometry  
MULTIPOLYGON (((36.76646 -1...
```


02:00

Convex Hull


Simple definition: Get the outer-most coordinates of a shape and connect-the-dots.

Formal definition: A convex hull of a shape the smallest "convex set" that contains it. (A **convex set** is where a straight line can be drawn anywhere in the space and the space fully contains the line).

Convex



Not convex



Source: [Wikipedia](#)

Convex hull

In the below example, we create a convex hull around schools; creating a polygon that includes all schools.

Incorrect attempt


```
schools_chull1_sf <- schools_sf %>%  
  st_convex_hull()  
  
nrow(schools_chull1_sf)
```

```
## [1] 3546
```

Convex hull


Correct

```
schools_chull2_sf <- schools_sf %>%  
  summarise(geometry = st_combine(geometry)) %>%  
  st_convex_hull()  
  
ggplot() +  
  geom_sf(data = schools_chull2_sf) +  
  geom_sf(data = schools_sf, color = "red")
```



Determine centroid

Sometimes we want to represent a polygon or polyline as a single point. For this, we can compute the centroid (ie, geographic center) of a polygon/polyline.



Source: [Wikipedia](#)


Determine centroid

Determine centroid of second administrative regions

```
country_c_sf <- st_centroid(country_sf)
```

```
## Warning: st_centroid assumes attributes are constant over geometries
```

```
ggplot() +  
  geom_sf(data = country_c_sf)
```



Remove geometry

Incorrect approach

```
city_sf %>%  
  select(-geometry) %>%  
  head()
```

```
## Simple feature collection with 6 features and 15 fields
```

```
## Geometry type: MULTIPOLYGON
```

```
## Dimension: XY
```

```
## Bounding box: xmin: 36.67803 ymin: -1.370704 xmax: 36.99025 ymax: -1.234921
```

```
## Geodetic CRS: WGS 84
```

##	GID_2	GID_0	COUNTRY	GID_1	NAME_1	NL_NAME_1	NAME_2	VARNAME_2	NL_NAME_2	TYPE_2
## 1	KEN.30.1_1	KEN	Kenya	KEN.30_1	Nairobi	<NA>	Dagoretti North	<NA>	<NA>	Constituency
## 2	KEN.30.2_1	KEN	Kenya	KEN.30_1	Nairobi	<NA>	Dagoretti South	<NA>	<NA>	Constituency
## 3	KEN.30.3_1	KEN	Kenya	KEN.30_1	Nairobi	<NA>	Embakasi Central	<NA>	<NA>	Constituency
## 4	KEN.30.4_1	KEN	Kenya	KEN.30_1	Nairobi	<NA>	Embakasi East	<NA>	<NA>	Constituency
## 5	KEN.30.5_1	KEN	Kenya	KEN.30_1	Nairobi	<NA>	Embakasi North	<NA>	<NA>	Constituency
## 6	KEN.30.6_1	KEN	Kenya	KEN.30_1	Nairobi	<NA>	Embakasi South	<NA>	<NA>	Constituency

##	ENGTYPE_2	CC_2	HASC_2	area_m	area_km	geometry
## 1	Constituency	275	<NA>	26850519	26.850519	MULTIPOLYGON (((36.76082 -1...
## 2	Constituency	276	<NA>	28881788	28.881788	MULTIPOLYGON (((36.75381 -1...

Remove geometry

Correct

```
city_sf %>%  
  st_drop_geometry() %>%  
  head()
```

##	GID_2	GID_0	COUNTRY	GID_1	NAME_1	NL_NAME_1	NAME_2	VARNAME_2	NL_NAME_2	TYPE_2
## 1	KEN.30.1_1	KEN	Kenya	KEN.30_1	Nairobi	<NA>	Dagoretti North	<NA>	<NA>	Constituency
## 2	KEN.30.2_1	KEN	Kenya	KEN.30_1	Nairobi	<NA>	Dagoretti South	<NA>	<NA>	Constituency
## 3	KEN.30.3_1	KEN	Kenya	KEN.30_1	Nairobi	<NA>	Embakasi Central	<NA>	<NA>	Constituency
## 4	KEN.30.4_1	KEN	Kenya	KEN.30_1	Nairobi	<NA>	Embakasi East	<NA>	<NA>	Constituency
## 5	KEN.30.5_1	KEN	Kenya	KEN.30_1	Nairobi	<NA>	Embakasi North	<NA>	<NA>	Constituency
## 6	KEN.30.6_1	KEN	Kenya	KEN.30_1	Nairobi	<NA>	Embakasi South	<NA>	<NA>	Constituency
##	ENGTYPE_2	CC_2	HASC_2	area_m	area_km					
## 1	Constituency	275	<NA>	26850519	26.850519					
## 2	Constituency	276	<NA>	28881788	28.881788					
## 3	Constituency	284	<NA>	8249195	8.249195					
## 4	Constituency	285	<NA>	86236564	86.236564					
## 5	Constituency	283	<NA>	5451808	5.451808					
## 6	Constituency	282	<NA>	17635838	17.635838					

Grab coordinates

Create a matrix of coordinates

```
schools_sf %>%  
  st_coordinates() %>%  
  head()
```

```
##           X           Y  
## [1,] 36.80406 -1.267486  
## [2,] 36.79734 -1.259690  
## [3,] 36.77077 -1.290325  
## [4,] 36.76877 -1.296051  
## [5,] 36.79066 -1.258515  
## [6,] 36.77899 -1.264575
```

Get bounding box

```
schools_sf %>%  
  st_bbox()
```

```
##      xmin      ymin      xmax      ymax  
## 36.691965 -1.374473 37.065336 -1.177316
```

Spatial operations using multiple datasets

- `st_distance`: Calculate distances.
- `st_intersects`: Indicates whether simple features intersect.
- `st_intersection`: Cut one spatial object based on another.
- `st_difference`: Remove part of spatial object based on another.
- `st_join`: Spatial join (ie, add attributes of one dataframe to another based on location).

Distances

For this example, we'll compute the distance between each school to a motorway.

```
motor_sf <- roads_sf %>%  
  filter(highway == "motorway")  
  
# Matrix: distance of each school to each motorway  
dist_mat <- st_distance(schools_sf, motor_sf)  
  
# Take minimum distance for each school  
dist_mat %>% apply(1, min) %>% head()  
  
## [1] 33.78464 155.32799 4006.16459 4662.68796 176.10524 1382.28513
```

Exercise

Exercise: Calculate the distance from the centroid of each second administrative division to the nearest trunk road.

Solution:

```
city_cent_sf <- city_sf %>% st_centroid()
```

```
## Warning: st_centroid assumes attributes are constant over geometries
```

```
trunk_sf <- roads_sf %>%  
  filter(highway == "trunk")
```

```
# Matrix: distance of each school to each motorway
```

```
dist_mat <- st_distance(city_cent_sf, trunk_sf)
```

```
# Take minimum distance for each school
```

```
dist_mat %>% apply(1, min) %>% head()
```

02:00

27.34582 2215.07338 929.39785 5642.60850 2015.55906 19.97698

Distances

```
# s2
st_distance(schools_sf[1,], schools_sf[2,]) %>%
  as.numeric()
```

```
## [1] 1144.271
```

```
# Nigeria-specific CRS
schools_utm_sf <- st_transform(schools_sf, 32632)
st_distance(schools_utm_sf[1,], schools_utm_sf[2,]) %>%
  as.numeric()
```

```
## [1] 1290.671
```

```
# World mercator
schools_merc_sf <- st_transform(schools_sf, 3395)
st_distance(schools_merc_sf[1,], schools_merc_sf[2,])
  as.numeric()
```

```
## [1] 1141.436
```

```
# Haversine
distHaversine(
  p1 = schools_sf[1,] %>% st_coordinates,
  p2 = schools_sf[2,] %>% st_coordinates)
```

```
## [1] 1145.551
```

```
# Vincenty's method
distVincentySphere(
  p1 = schools_sf[1,] %>% st_coordinates,
  p2 = schools_sf[2,] %>% st_coordinates)
```

```
## [1] 1145.551
```

```
# Karney's method
distGeo(p1 = schools_sf[1,] %>% st_coordinates,
        p2 = schools_sf[2,] %>% st_coordinates)
```

```
## [1] 1141.16
```

Intersects

For this example we'll determine which second administrative divisions intersects with a motorway.

```
# Sparse matrix
```

```
st_intersects(city_sf, motor_sf) %>% print()
```

```
## Sparse geometry binary predicate list of length 17, where the predicate was `intersects'
```

```
## first 10 elements:
```

```
## 1: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, ...
```

```
## 2: (empty)
```

```
## 3: (empty)
```

```
## 4: 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, ...
```

```
## 5: (empty)
```

```
## 6: 30, 32, 33, 34, 35, 36, 37, 38, 39, 40, ...
```

```
## 7: (empty)
```

```
## 8: (empty)
```

```
## 9: (empty)
```

```
## 10: 10, 42, 43, 45, 64
```

Intersects

Take `max` (`FALSE` corresponds to 0 and `TRUE` corresponds to 1). So taking max will yeild if unit intersects with *any* motorway

```
# Matrix
st_intersects(city_sf, motor_sf, sparse = F) %>%
  apply(1, max) %>%
  head()
```

```
## [1] 1 0 0 1 0 1
```

Exercise

Exercise: Determine which motorways intersect with a trunk road

Solution:

```
trunk_sf <- roads_sf %>% filter(highway == "trunk")
motor_sf <- roads_sf %>% filter(highway == "motorway")

st_intersects(motor_sf, trunk_sf, sparse = F) %>%
  apply(1, max) %>%
  head()
```

02:00


Intersection

We have roads for the full city. Here, we want to create new roads object that **only includes** roads in one unit.

```
loc_sf <- city_sf %>%  
  head(1)  
  
roads_loc_sf <- st_intersection(roads_sf, loc_sf)
```

Warning: attribute variables are assumed to be spatially constant throughout all geometries

```
ggplot() +  
  geom_sf(data = roads_loc_sf)
```




Difference

We have roads for all of the city. Here, we want to create new roads object that **excludes** roads in one unit.

```
roads_notloc_sf <- st_difference(roads_sf, loc_sf)
```


```
## Warning: attribute variables are assumed to be spatially constant throughout all geometries
```

```
ggplot() +  
  geom_sf(data = loc_sf, fill = NA, color = "red") +  
  geom_sf(data = roads_notloc_sf)
```




Overlay


Intersections and differencing are **overlay** functions




Intersection



Union



Symmetrical Difference



Difference

Exercise

Exercise: Create a map of schools that are within 1km of a motorway.

Solution:

```
motor_1km_sf <- roads_sf %>%  
  filter(highway == "motorway") %>%  
  st_buffer(dist = 1000)  
  
schools_nr_motor_sf <- schools_sf %>%  
  st_intersection(motor_1km_sf)  
  
leaflet() %>%  
  addTiles() %>%  
  addCircles(data = schools_nr_motor_sf)
```

02:00

Exercise

Note that there are multiple approaches we could have used for creating a map of schools that are within 1km of a trunk road.

1. Buffer trunk roads by 1km and do a spatial intersection with schools
2. Calculate the distance of each school to the nearest trunk road, then filter schools that are within 1km of a trunk road

Spatial join

We have a dataset of schools. The school dataframe contains information such as the school name, but not on the administrative region it's in. To add data on the administrative region that the school is in, we'll perform a spatial join.

Check the variable names. No names of second administrative division :(

```
names(schools_sf)
```

```
## [1] "osm_id"  "name"    "amenity" "geometry"
```

Spatial join

Use `st_join` to add attributes from `city_sf` to `schools_sf`. `st_join` is similar to other join methods (eg, `left_join`); instead of joining on a variable, we join based on location.

```
schools_city_sf <- st_join(schools_sf, city_sf)
```

```
schools_city_sf %>%
```

```
  names() %>%
```

```
  print() %>%
```

```
  tail(10)
```

```
## [1] "osm_id"      "name"        "amenity"     "geometry"    "GID_2"       "GID_0"       "COUNTRY"     "GID_1"       "NAME_1"
## [10] "NL_NAME_1"   "NAME_2"      "VARNAME_2"   "NL_NAME_2"   "TYPE_2"      "ENGTYPE_2"   "CC_2"        "HASC_2"      "area_m"
## [19] "area_km"
```

```
## [1] "NL_NAME_1"   "NAME_2"      "VARNAME_2"   "NL_NAME_2"   "TYPE_2"      "ENGTYPE_2"   "CC_2"        "HASC_2"      "area_m"
## [10] "area_km"
```

Spatial join

Exercise: Make a static map using of administrative areas, where each administrative area polygon displays the number of schools within the administrative area.

Solution:


```
## Dataframe of number of schools per NAME_2
n_school_df <- schools_city_sf %>%
  st_drop_geometry() %>%
  group_by(NAME_2) %>%
  summarise(n_school = n()) %>%
  ungroup()

## Merge info with city_sf
city_sch_sf <- city_sf %>% left_join(n_school_df, by = "NAME_2")

## Map
p <- ggplot() +
  geom_sf(data = city_sch_sf,
    aes(fill = n_school))
```

Spatial join

```
ggplot() +  
  geom_sf(data = city_sch_sf,  
          aes(fill = n_school)) +  
  labs(fill = "N\nSchools") +  
  scale_fill_distiller(palette = "YlOrRd") +  
  theme_void()
```



Spatial join

Let's outsource to [chatGPT](#) (or [gemini](#) or your other favorite AI). Try entering the below prompt into chatGPT to see how it does. Does chatGPT give a correct answer? Do you need to modify chatGPT's output to make it work?

In R, I have an sf points object of schools called schools_sf. I also have the second administrative divisions of a city as an sf polygon called city_sf and where each location is uniquely defined by the variable NAME_2. Make a static map using of administrative areas, where each administrative area polygon displays the number of schools within the administrative area. Provide R code for this.

Resources

- [sf package cheatsheet](#)
- [Spatial Data Science with Applications in R](#)
- [Geocomputation with R](#)

Thank you!

